Linea Combinata 2,0 x 1500 mm / COMBINED LINE 2.0 x 1500 mm



- **Thickness range:** from 0.4 mm to 2.0 mm (Aluminum up to 3.0 mm)
- **Slitting system:** movable blades mounted on arbors
- **Arbor diameter:** 120 mm
- **Loading/unloading:** max 10 tons
- **Max loading diameter:** 1,900 mm
- **Mandrel expansion (inner bore):** 500 mm
- **Leveling:** 7-roller leveling unit (diameter 100 mm)
- **Shear:** hydraulic
- **Slitter cutting speed:** 50 m/min
- **Min. slitting width:** 150 mm
- **Min. leveling width:** 120 mm
- **Max. leveling length:** 6.0 m
- **Leveling table:** with motorized rollers
- **Scrap management:** double friction scrap winder for continuous operation
- **Drive system:** inverter-driven leveling unit
- **Recoiling:** recoiler mandrel with comb and belt tensioners
- **Certification:** fully CE marked
- **Safety:** perimeter guarding and protections included

SIDICOM
Sede Amm/Comm.:
Via Bachelet, 20
35010 LIMENA (PD) -ITALY

Sede Amm/Comm.:
Via Bachelet, 20
35010 LIMENA (PD) -ITALY

Tel. +39 049 769998 - Fax. +39 049 767778
www.sidicom.it - email: commerciale@sidicom.it